


Drawings are not to scale.

QuickEdge® Decorative Protective Trim


Flexible Embossed Vinyl Aluminum Core QuickEdge® Trims

1/2" Trim

 for 3/8" to 1/2" Edges
 Grips edges from
 .250" to .500" thick



PART NO.	DESCRIPTION	CARTON FEET
75001582	Black Sof-Tone	150
75001620	White Sof-Tone	150

Pinch Top Single Lip Trim

 for 1/8" Edges
 Grips edges from
 .060" to .170" thick



PART NO.	DESCRIPTION	CARTON FEET
75001585	Black Sof-Tone	400
75001623	White Sof-Tone	400

"Q" Trim

 for 3/16" to 1/4" Edges
 Grips edges from
 .135" to .250" thick



PART NO.	DESCRIPTION	CARTON FEET
75001583	Black Sof-Tone	250
75001621	White Sof-Tone	250

Standard Double Lip Trim

 for 1/32" to 1/8" Edges
 Grips edges from
 .032" to .125" thick



PART NO.	DESCRIPTION	CARTON FEET
75001584	Black Sof-Tone	400
75001622	White Sof-Tone	400

Standard Single Lip Trim

 for 1/8" to 3/16" Edges
 Grips edges from
 .090" to .190" thick


PART NO.	DESCRIPTION	CARTON FEET
75000346	White Sof-Tone	400
75000348	Black Sof-Tone	400
75001234	White Sof-Tone	100
75001309	Black Sof-Tone	100

Minitrim

 for 1/32" Edges
 Grips edges from
 .010" to .050" thick


PART NO.	DESCRIPTION	CARTON FEET
75001586	Black Sof-Tone	500
75001624	White Sof-Tone	500

Advantages and Physical Characteristics

Environmentally Safe Vinyl - Embossed PVC extrusions with non-cadmium stabilizers

Segmented Aluminum Core - Type 50-52 Rockwell 38, .024" thick

Flexible Durometer - All parts are 65 durometer except the Standard Double Lip Trims which are 80 durometer hardness (share A 15 second delay)

Tensile Strength - 2200 P.S.I. / Minimum

Elongation - 300% minimum

Cold Impact - Will withstand 1-1/2 foot pound impact at -20° F

Heat Resistance - 150° F maximum for continuous use

Flammability - Self extinguishing, passes Federal Spec. FMVSS-302

